



SPECIFICATION SHEET

Description: Heavy-duty Interlocking porous plastic paving grids for ground reinforcement. Suitable for trafficking applications including HGVs, forklift trucks, industrial yards, coach parks, car parking, paths, walkways and fire access lanes.

Truckgrid paving grids provide a stable reinforced permeable load-bearing surface.

CHARACTERISTICS	DATA
Dimensions	500mm x 400mm wide x 37mm
Weight	Each piece is 2.1kg - 10.5kg per m ²
Nominal cell dimensions	60mm Octagonal
Locking and anti shear	10 locking connections per pc
Connection method	Interlocking block and groove
Cell wall thickness	5mm
Cell Openness %	90% on top and 60% on base
Polymer	Recycled Polyethylene
Colour	Black
UV Stabilised	Yes
Load bearing capacity(filled)	10 tonne per wheel / 20 tonne axle load
Environmentally neutral	Yes
Production control	Under ISO Control
Traffic Loading	Tested to DIN 1072
Pavers per m ²	Five

All data figures are nominal and are given in good faith. All Stake Supply reserves the right to amend any data without prior notice. Product variances are provided as a guide and normal production and product characteristics are within these parameters.

Please note that the information above is given as a guide only. All Stake Supply cannot be liable for damage caused by incorrect installation of this product. Final determination of the suitability of any information or material for the use contemplated and the manner of its use is the sole responsibility of the user and the user must assume all risk and responsibility in connection therewith.